

CLAIMS

1. An electronic apparatus comprising:

a case constituting an armor; and

a component part containing chamber in which a component part is removably contained through a first opening provided in the inside of said case and opened in an outside surface of said case; wherein

a second opening is provided in a wall portion forming said component part containing chamber;

a component part containing space communicated with said second opening is provided in the inside of said case;

a holder is provided which comprises a first plate portion detachably attached to said second opening so as to shut off said second opening, and a second plate portion projecting from said first plate portion and extending in said component part containing space in the condition where said first plate portion shuts off said second opening;

a separable body is held in said holder; and

said first opening, said component part containing chamber, and said second opening are formed in such sizes that said holder with said separable body held in said holder can be moved from said component part

containing space to the exterior of said case.

2. An electronic apparatus as set forth in claim 1, wherein said separable body is a secondary battery or electric component part which must be separated from said electronic apparatus at the time of discarding said electronic apparatus.

3. An electronic apparatus as set forth in claim 1, wherein the surface of said first plate portion is so formed as to be flush with a wall surface in the periphery of said second opening in the condition where said first plate portion shuts off said second opening.

4. An electronic apparatus as set forth in claim 1, wherein an end portion of said first plate portion fronts on said first opening in the condition where said first plate portion shuts off said second opening, and a groove is formed in said end portion, fronting on said first opening, of said first plate portion.

5. An electronic apparatus as set forth in claim 4, wherein said groove is so formed that a hooking means such as a minus screw driver is locked therein.

6. An electronic apparatus as set forth in claim 1, wherein said second opening is provided in the vicinity of said first opening.

7. An electronic apparatus as set forth in claim

1, wherein said component part containing chamber is a chamber for containing a storage type battery or dry battery for supplying said electronic apparatus with electric power.

8. An electronic apparatus as set forth in claim 1, wherein said component part containing chamber is a chamber for containing a storage medium for transfer of data between the storage medium and said electronic apparatus, or for containing an adapter operated by being electrically connected to said electronic apparatus.

9. An electronic apparatus as set forth in claim 1, wherein said separable body is connected to a circuit portion provided in said electronic apparatus through a flexible substrate or lead wires, and said flexible substrate or lead wires are broken when said separable body is drawn out from said containing space to the exterior of said case together with said holding member.

10. An electronic apparatus as set forth in claim 1, wherein an opening/closing lid is provided for opening and closing said first opening.

11. An electronic apparatus as set forth in claim 1, wherein said component part containing chamber is provided in a housing incorporated in said case, and said wall portion, said first opening and said second

S04P1452

opening are provided in said housing.